Voronoi diagrams

Computational Geometry

Lecture 10: Voronoi diagrams

Voronoi diagrams Spatial interpolation

Voronoi diagram

Given some trees, seen from above, which region will they occupy?



Voronoi diagrams Spatial interpolation

Voronoi diagram

Given some trees, seen from above, which region will they occupy?



Voronoi diagrams Spatial interpolation

Voronoi diagram

Given ambulance posts in a country, in case of an emergency somewhere, where should the ambulance come from?



Voronoi diagrams Spatial interpolation

Voronoi diagram

Given ambulance posts in a country, in case of an emergency somewhere, where should the ambulance come from?



Voronoi diagram induced by a set of points (called sites): Subdivision of the plane where the faces correspond to the regions where one site is closest

Voronoi diagrams Spatial interpolation

Voronoi diagram



Voronoi diagram

Question: Why is the Voronoi diagram not really a subdivision?

Voronoi diagrams Spatial interpolation

Spatial interpolation

Suppose we tested the soil at a number of sample points and classified the results



Voronoi diagrams Spatial interpolation

Spatial interpolation

Suppose we tested the soil at a number of sample points and classified the results



Voronoi diagrams Spatial interpolation

Spatial interpolation

Suppose we tested the soil at a number of sample points and classified the results



Voronoi diagrams Spatial interpolation

Spatial interpolation



Voronoi diagrams Spatial interpolation

Spatial interpolation



Voronoi diagrams Spatial interpolation

Spatial interpolation



Voronoi diagrams Spatial interpolation

Spatial interpolation



Voronoi diagrams Spatial interpolation

Spatial interpolation



Voronoi diagrams Spatial interpolation

Spatial interpolation

Let
$$A_T = A_1 + A_2 + \dots + A_5$$

The interpolated value is

$$\frac{A_1}{A_T}$$
 13 + $\frac{A_2}{A_T}$ 11 + ... + $\frac{A_5}{A_T}$ 20



Voronoi diagrams Spatial interpolation

Spatial interpolation



Crater on Mars generated by natural neighbor interpolation

Properties Construction

Some observations

Edges are parts of bisectors Some edges are half-infinite Some cells are unbounded

Question: Which ones?



Properties Construction

Some observations

Every Voronoi cell is the intersection of n-1 half-planes, if there are n sites

 \Rightarrow all cells are convex and have up to n-1 edges in the boundary



The Voronoi diagram of n sites has the following structure:

- If all *n* sites lie on a line, then the Voronoi cell boundaries are parallel lines, so the "graph" is disconnected
- Otherwise, the Voronoi cell boundaries form a connected "graph"

Theorem: The Voronoi diagram on f sites in the plane has at most 2n-5 Voronoi vertices and at most 3n-6 Voronoi edges (including lines and half-lines)

Proof: If the sites are colinear, then it is trivial

Otherwise, we will use Euler's formula for planar graphs

Euler's formula for planar graphs: A connected planar graph with n_v vertices, n_e edges, and n_f faces satisfies:

$$n_v - n_e + n_f = 2$$

However, a Voronoi diagram is not a proper graph

Properties Construction

We make it proper by connecting all half-infinite edges to a new vertex v_{∞}

 $n_v =$ no. of Voronoi vertices VV + 1

 $n_e =$ no. of Voronoi edges VE

 $n_f =$ no. of Voronoi cells = n, the number of sites



Motivation Pr Voronoi diagrams Co

Properties Construction

Substitution in Euler's formula $n_v - n_e + n_f = 2$ gives

$$(VV+1) - VE + n = 2$$

Every edge is incident to exactly 2 vertices, and every vertex is incident to at least 3 edges

Sum-of-degree-of-all-vertices $= 2 \cdot VE$

Sum-of-degree-of-all-vertices $\geq 3 \cdot VV$

$$= 2 \cdot VE \ge 3 \cdot VV$$

The combination of

$$(VV+1) - VE + n = 2$$

and

Complexity

$$= 2 \cdot VE \ge 3 \cdot VV$$

gives the desired bounds $VV \leq 2n-5$ and $VE \leq 3n-6$

Properties Construction

Empty circle property

Every Voronoi vertex is the center of an empty circle through 3 sites

Every point on a Voronoi edge is the center of an empty circle through 2 sites



Properties Construction

Degeneracies

All sites lie on a line

More than 3 points lie on a circle



Algorithms for Voronoi diagrams

Compute the intersection of n-1 half-planes for each site, and "merge" the cells into the diagram

Divide-and-conquer (1975, Shamos & Hoey)

Plane sweep (1987, Fortune)

Randomized incremental construction (1992, Guibas, Knuth & Sharir)

Plane sweep: Note that the Voronoi diagram above the sweep line may be affected by sites below the sweep line

Motivation

Maintain and grow the portion of Voronoi diagram above the sweep line that is *known for sure*



Plane sweep: Note that the Voronoi diagram above the sweep line may be affected by sites below the sweep line

Motivation

Maintain and grow the portion of Voronoi diagram above the sweep line that is *known for sure*



The beach line separates the known and unknown part of the Voronoi diagram, it is the minimum of the parabolas defined by sites above the sweep-line and the sweep-line itself



Properties Construction

The beach line changes continuously, even one parabola does



Beach line

Beach line

Question: The beach line has break points, what do they represent?



Properties Construction

Beach line

The break points move and trace out the Voronoi diagram edges



Status: The ordered sequence of parabolic arcs that define the beach line; each is defined by a site (and the sweep-line)

Break points are defined by two sites (and the sweep-line)

Since the beach line is *x*-monotone, we can store the status in a balanced binary search tree on *x*-coordinate
Properties Construction





Other data structures

The sweep algorithm also needs an **event list** and a data structure to store the Voronoi diagram computed so far

The Voronoi diagram will be computed inside a large bounding box so that a doubly-connected edge list can be used

The events are where the status $\mbox{changes} = \mbox{where the beach}$ line $\mbox{changes}$

- When the sweep-line reaches a new site
- When a break point reaches the end of the edge it traces

Properties Construction

Site events



Site events



Site events



- Two new break points appear on the beach line
- A new Voronoi edge is discovered



Properties Construction



Properties Construction



Properties Construction



Properties Construction



Properties Construction



Properties Construction



Properties Construction



Properties Construction



Parabolic arcs may disappear from the beach line



We discover an empty circle and a Voronoi vertex



Circle events

At a circle event:

- A parabolic arc disappears from the beach line
- Two adjacent break points come together
- A Voronoi vertex is discovered as the vertex incident to two known Voronoi edges
- A new break point starts to be traced
- The sweep line reached the bottom of an empty circle through 3 sites

Properties Construction

Circle events



Circle events can only happen for three sites that have adjacent parabolic arcs on the beach line

Site and circle events

The only way for a new parabolic arc to **appear** on the beach line is through a **site event**

The only way for a parabolic arc to **disappear** from the beach line is through a **circle event**

There are no other events

Site and circle events

There are n site events and they are known in advance

Question: How can we know circle events before they occur?

Properties Construction

Detecting circle events



Properties Construction

Detecting circle events



Detecting circle events

A circle event occurs if the sweep line reaches the bottom of an empty circle defined by three sites that have consecutive parabolic arcs on the beach line

We will make sure that any three sites that have consecutive arcs on the beach line and whose circle has its lowest point below the sweep line have this lowest point as circle event in the event list

Properties Construction

Detecting circle events

In the status structure we can see all triples of consecutive parabolic arcs that can give circle events



We may have stored a circle event in the event list, but it may be that it never happens ...

This is called a false alarm

There are two reasons for false alarms: site events and other circle events

Properties Construction

False alarms



Properties Construction

False alarms



The circle of a circle event may turn out not to be empty

Detecting false alarms

A site event that disrupts three consecutive parabolic arcs



Properties Construction

Detecting false alarms



Detecting false alarms

A site event that disrupts three consecutive parabolic arcs



circle event $C(p_2, p_3, p_4)$ gone

Detecting false alarms

A circle event that disrupts three consecutive parabolic arcs



Properties Construction

Detecting false alarms



Properties Construction

Detecting false alarms

A circle event that disrupts three consecutive parabolic arcs



The data structures

Recall we have a status structure $\ensuremath{\mathbb{T}}$, an event list, and a DCEL

We need pointers from $\ensuremath{\mathbb{T}}$ into the DCEL to be able to update it efficiently

We need pointers from the leaves of $\ensuremath{\mathbb{T}}$ into the event list to be able to remove circle events if they are false alarms

The data structures

A leaf of $\ensuremath{\mathbb{T}}$ has a pointer to all events in which the parabolic arc participates

Easy question: How many can there be, at most?
Global algorithm

Algorithm VORONOIDIAGRAM(*P*)

- 1. Initialize the event queue Ω with all site events, initialize an empty status structure T and an empty doubly-connected edge list D
- 2. while Q is not empty
- 3. **do** remove the event with largest *y*-coordinate from Ω
- 4. **if** the event is a site event, occurring at site p_i
- 5. **then** HANDLESITEEVENT (p_i)
- 6. else HANDLECIRCLEEVENT(γ), where γ is the leaf of \mathcal{T} representing the arc that will disappear
- 7. When all events are handled, we must still fix the doubly-connected edge list with respect to the bounding box, and to add face information

Site event actions

At a site event, at a site p_i on the sweep line ℓ :

- Find the parabolic arc α vertically above p_i in \mathfrak{T}
- Remove the false alarm with α in the middle from the event list (if it exists)
- Update \mathcal{T} : one arc is split and a new one for p_i appears in between, and break points are updated
- Make two new half-edges for the detected Voronoi edge in the DCEL
- Add new circle events for the new consecutive triples (if the circle has its lowest point below ℓ)

Properties Construction

Circle event actions

At a circle event, for circle $C(p_i, p_j, p_k)$ whose bottom is on the sweep line ℓ , and γ is the leaf of \mathfrak{T} whose arc disappears:

- Remove the false alarms that involve the parabolic arc corresponding to γ
- Update \mathfrak{T} : remove the leaf γ and update break points
- Make a new vertex object for the Voronoi vertex, two new half-edge objects, and connect six half-edges and the vertex in the DCEL
- Add new circle events for the new consecutive triples (if the circle has its lowest point below ℓ)

Any event removes at most two false alarms and generates at most two new circle events

Any event is handled in $O(\log n)$ time

There are *n* site events and at most 2n-5 circle events (because a new Voronoi vertex is detected)



Theorem: The Voronoi diagram of a set of n point sites in the plane can be computed in $O(n \log n)$ time

	=	
v	-	